

TABLE OF CONTENTS

FOREWORD	iii
SMACNA DUCT DESIGN COMMITTEE	iv
NOTICE TO USERS	v
TABLE OF CONTENTS	vii

CHAPTER 1	INTRODUCTION	Page
1.1	SCOPE	1.1
1.2	HOW TO USE THIS MANUAL	1.1
1.3	PURPOSE	1.1
1.4	HISTORY OF AIR DUCT SYSTEMS	1.1
1.5	GENERAL REQUIREMENTS	1.2
1.6	HVAC SYSTEMS LIBRARY	1.2
1.7	CODES AND ORDINANCES	1.3
1.8	HVAC DUCT SYSTEM TYPES	1.5
1.9	SMOKE CONTROL SYSTEMS	1.6
1.10	INDOOR AIR QUALITY	1.7
1.11	VENTILATION RATES	1.8
CHAPTER 2	ECONOMICS OF DUCT SYSTEMS	
2.1	SCOPE	2.1
2.2	RESPONSIBILITIES	2.1
2.3	INITIAL SYSTEM COSTS	2.2
2.4	ANNUAL OWNING COSTS	2.3
2.5	ANNUAL OPERATING COSTS	2.3
2.6	OPERATION COSTS	2.3
2.7	CONTROLLING COSTS	2.5
2.8	DUCT ASPECT RATIOS	2.5
2.9	PRESSURE CLASSIFICATION AND LEAKAGE	2.5
2.10	COST OF FITTINGS	2.7
CHAPTER 3	ROOM AIR DISTRIBUTION	
3.1	SCOPE	3.1
3.2	COMFORT	3.1
3.3	AIR DISTRIBUTION FUNDAMENTALS	3.13
3.4	OUTLET LOCATION	3.15
3.5	OUTLET CRITERIA	3.20
3.6	GRILLE AND REGISTER APPLICATIONS	3.20
3.7	SLOT DIFFUSER APPLICATIONS	3.20
3.8	CEILING DIFFUSER APPLICATIONS	3.21
3.9	OUTLETS IN VARIABLE AIR VOLUME (VAV) SYSTEMS	3.23
3.10	INLET CRITERIA	3.23
3.11	EXHAUST OUTLETS	3.25
3.12	SPECIAL SITUATIONS	3.25
3.13	AIR DISTRIBUTION SUMMARY	3.25
3.14	ROOM TERMINAL DEVICES	3.26
3.15	SUPPLY AIR GRILLE AND REGISTER TYPES	3.28
3.16	SUPPLY AIR CEILING DIFFUSER TYPES	3.28
3.17	VAV AND THERMAL BOXES	3.29



3.18	TERMINAL BOX VARIATIONS	3.30
3.19	BASIC VAV SYSTEM DESIGN	3.31
3.20	VAV COMPONENTS AND CONTROLS	3.32
3.21	VAV SYSTEM ADVANTAGES	3.33
3.22	VAV SYSTEM DESIGN PRECAUTIONS	3.33
3.23	VAV TERMINAL DEVICES	3.35

CHAPTER 4 GENERAL APPROACH TO DUCT DESIGN Page

4.1	SCOPE	4.1
4.2	DESIGN METHODS – OVERVIEW	4.3
4.3	SELDOM USED METHODS	4.4
4.4	DUCT HEAT GAIN OR LOSS	4.5
4.5	SOUND AND VIBRATION	4.5
4.6	PRESSURE CLASSIFICATION	4.5
4.7	DUCT LEAKAGE	4.6
4.8	FAN SIZING	4.6
4.9	TESTING, ADJUSTING AND BALANCING (TAB)	4.6
4.10	FINAL DESIGN DOCUMENTS	4.6

CHAPTER 5 DUCT DESIGN FUNDAMENTALS

5.1	SCOPE	5.1
5.2	FLUID PROPERTIES	5.1
5.3	FLUID STATICS	5.2
5.4	FLUID DYNAMICS	5.3
5.5	FLUID FLOW PATTERNS	5.6
5.6	DUCT SYSTEM PRESSURES	5.9
5.7	FRICTION LOSSES	5.10
5.8	DYNAMIC LOSSES	5.12
5.9	BASIC DUCT SIZING	5.14
5.10	DUCT CONFIGURATIONS	5.16
5.11	DUCT FITTINGS	5.18
5.12	SYSTEM PRESSURE CHANGES	5.22
5.13	STRAIGHT DUCT LOSSES	5.25
5.14	DYNAMIC LOSSES	5.25
5.15	SPLITTER VANES	5.27
5.16	TURNING VANES	5.27
5.17	PRESSURE LOSSES IN DIVIDED-FLOW FITTINGS	5.30
5.18	LOSSES DUE TO AREA CHANGES	5.31
5.19	OTHER LOSS COEFFICIENTS	5.31
5.20	OBSTRUCTION AVOIDANCE	5.32
5.21	DUCT AIR LEAKAGE	5.34
5.22	DUCT HEAT GAIN/LOSS	5.38
5.23	SMACNA DUCT RESEARCH	5.40
5.24	FAN PRESSURES	5.41
5.25	FAN DEFINITIONS	5.42
5.26	FAN LAWS	5.44
5.27	FAN TESTING	5.46
5.28	FAN CLASSIFICATIONS	5.46
5.29	FAN TYPES	5.46
5.30	FAN CURVES	5.49
5.31	DUCT SYSTEM AIRFLOW	5.52
5.32	SYSTEM CURVES	5.52
5.33	AIR DENSITY EFFECTS	5.56
5.34	ESTIMATING SYSTEM RESISTANCE	5.58
5.35	SAFETY FACTORS	5.59
5.36	THE FAN OUTLET	5.59



5.37	THE FAN INLET	5.63
5.38	ASHRAE METHODS	5.64
5.39	FUNDAMENTALS HANDBOOK	5.66
5.40	DEFICIENT FAN PERFORMANCE	5.67
5.41	SYSTEM EFFECT FACTORS	5.67
5.42	BUILDING PRESSURES	5.70
5.43	BUILDING AIRFLOW CONTROL	5.73
CHAPTER 6	FAN-DUCT CONNECTION PRESSURE LOSSES	Page
6.1	SCOPE	6.1
6.2	FAN OUTLET CONDITIONS	6.1
6.3	FAN INLET CONDITIONS	6.7
6.4	EFFECTS OF FACTORY SUPPLIED ACCESSORIES	6.13
6.5	CALCULATING SYSTEM EFFECT	6.16
CHAPTER 7	DUCT SIZING PROCEDURES	
7.1	SCOPE	7.1
7.2	DESIGN OBJECTIVES	7.1
7.3	DUCT SYSTEM SIZING PROCEDURES	7.1
7.4	FITTING PRESSURE LOSS TABLES	7.2
7.5	SUPPLY AIR DUCT SYSTEM-SIZING EXAMPLE 1 (I-P)	7.4
7.6	RETURN AIR (EXHAUST AIR) DUCT SYSTEM-SIZING EXAMPLE 2	7.18
7.7	SUPPLY AIR DUCT SYSTEM SIZING EXAMPLE 3 (I-P)	7.21
7.8	EXTENDED PLENUM DUCT SIZING	7.26
7.9	DESIGN FUNDAMENTALS (SI)	7.32
7.10	SUPPLY AIR DUCT SYSTEM – SIZING EXAMPLE. 1 (SI)	7.32
7.11	RETURN AIR (EXHAUST AIR) DUCT SYSTEM-SIZING EXAMPLE 2 (SI)	7.40
7.12	SUPPLY AIR DUCT SYSTEM SIZING EXAMPLE 3 (SI)	7.47
7.13	EXTENDED PLENUM DUCT SIZING	7.52
CHAPTER 8	PRESSURE LOSS OF SYSTEMS COMPONENTS	
8.1	SCOPE	8.1
8.2	USE OF TABLES AND CHARTS	8.1
8.3	DAMPER CHARTS	8.8
8.4	DUCT SYSTEM APPARATUS CHARTS	8.9
8.5	ROOM AIR TERMINAL DEVICES	8.15
8.6	LOUVER DESIGN DATA	8.17
CHAPTER 9	PROVISIONS FOR TESTING, ADJUSTING, AND BALANCING	
9.1	SCOPE	9.1
9.2	TAB DESIGN CONSIDERATIONS	9.1
9.3	AIR MEASUREMENT DEVICES	9.5
9.4	BALANCING WITH ORIFICES	9.5
9.5	PROVISIONS FOR TAB IN SYSTEM DESIGN	9.5
9.6	LABORATORY TESTING	9.6
9.7	FIELD TESTING AND BALANCING	9.7
9.8	TEST INSTRUMENTATION	9.10



CHAPTER 10	DESIGNING FOR SOUND AND VIBRATION	Page
10.1	SCOPE	10.1
10.2	BUILDING NOISE	10.1
10.3	HVAC NOISE	10.2
10.4	COMMON SOUND SOURCES	10.6
10.5	SOUND DATA STANDARDS	10.7
10.6	DUCT NOISE	10.7
10.7	DUCT SILENCERS	10.8
10.8	ACOUSTIC LAGGING	10.10
10.9	DUCT SOUND BREAKOUT	10.10
CHAPTER 11	DUCT SYSTEM CONSTRUCTION	
11.1	SCOPE	11.1
11.2	DUCT SYSTEM SPECIFICATION CHECK LIST	11.1
11.3	DUCT CONSTRUCTION MATERIALS	11.1
11.4	ASTM STANDARDS	11.5
CHAPTER 12	SPECIAL DUCT SYSTEMS	
12.1	SCOPE	12.1
12.2	KITCHEN AND MOISTURE – LADEN SYSTEMS	12.1
12.3	SYSTEMS HANDLING SPECIAL GASES	12.1
12.4	INDUSTRIAL DUCT	12.1
APPENDIX A	DUCT DESIGN TABLES AND CHARTS	
	FITTING LOSS COEFFICIENT TABLES	A.15
	HVAC EQUATIONS (I-P)	A.51
	HVAC EQUATIONS (SI)	A.56
	SI UNITS AND EQUIVALENTS	A.59

INDEX



TABLES

Page

2-1	Annual Life Cycle Cost Factors	2.2
2-2	Cost of Owning and Operating a Typical Commercial Building	2.3
2-3	Initial Cost Systems	2.4
2-4	Aspect Ratio Example	2.5
2-5	Relative Duct System Costs (Fabrication and Installation of Same Size Duct)	2.7
2-6	Estimated Equipment Service Lives	2.8
3-1	Metabolic Rates of Typical Tasks	3.1
3-2	Operative Temperatures for Thermal Acceptability or Sedentary or Slightly Active Persons (≤ 1.2 Mets) At 50 Percent Relative Humidity ^a	3.4
3-3	Clo Units for Individual Items of Clothing = 0.82 (S Individual Items)	3.8
3-4	Characteristic Room Lengths for Diffusers	3.10
3-5	Air Diffusion Performance Index (ADPI)	3.12
3-6	Guide for Selection of Supply Outlets	3.17
3-7	Supply Air Outlet Types	3.22
3-8	Supply Air Outlet Performance	3.24
3-9	Recommended Return Air Inlet Face Velocities	3.26
3-10	Return and Exhaust Air Inlet Types	3.26
3-11	Accessory Devices	3.27
4-1	HVAC Duct Pressure Velocity Classification	4.5
5-1	Unsealed Longitudinal Seam Leakage for Metal Ducts	5.33
5-2	Applicable Leakage Classes ^a	5.36
5-3	Leakage as a Percentage of System Airflow	5.36
5-4	K Values for Outlet Ducts	5.65
5-5	K Values for Single Width, Single Inlet Fans (SWSI)	5.66
6-1	System Effect Curves for Outlet Ducts	6.4
6-2	System Effect Factor Curves for Outlet Elbows	6.6
6-3	System Effect Curves for Inlet Obstructions	6.16
6-4		6.17
7-1	Duct Sizing, Supply Air System – Example 1	7.6
7-1(a)	Duct Sizing, Supply Air System – Example 1 (Continued)	7.7
7-2	Duct Sizing, Exhaust Air System – Example 2 (I-P)	7.15
7-3	Duct Sizing, Exhaust Air System – Example 3 (I-P)	7.16
7-3(a)	Duct Sizing, Exhaust Air System – Example 3 (I-P) (Continued)	7.17
7-4	Semi-extended Plenum Comparison	7.28
7-5	Semi-extended Plenum Installation Cost Comparison	7.28
7-6	Duct Sizing, Supply Air System – Example 1	7.30
7-6(a)	Duct Sizing, Supply Air System – Example 1 (Continued)	7.31
7-7	Duct Sizing, Exhaust Air System – Example 2 (SI)	7.44
7-8	Duct Sizing, Supply Air System – Example 3	7.45
7-8(a)	Duct Sizing, Supply Air System – Example 3 (Continued)	7.46
7-9	Semi-extended Plenum Comparison	7.53
7-10	Semi-extended Plenum Installation Cost Comparison	7.53
8-1	Filter Pressure Loss Data	8.1
8-2	Louver Free Area Chart 2 in. Blades At 45 Degree Angle	8.4
8-3	Louver Free Area Chart 4 in. Blades At 45 Degree Angle	8.5
8-4	Louver Free Area Chart 6 in. Blades At 45 Degree Angle	8.6
8-5	Air Outlets & Diffusers – Total Pressure Loss Average	8.15
8-6	Supply Registers – Total Pressure Loss Average	8.15
8-7	Return Registers – Total Pressure Loss Average	8.15
8-8	Typical Design Velocities	8.16
9-1	Airflow Measuring Instruments	9.11
10-1	Sound Sources, Transmission Paths, and Recommended Noise Reduction Methods	10.5
11-1	Sheet Metal Properties	11.4



FIGURES

Page

1-1	U.S.A. Building Codes and Ordinances	1.4
2-1	Relative Costs of Duct Segments Installed	2.6
2-2	Relative Installed Cost Versus Aspect Ratio	2.6
2-3	Relative Operating Cost Versus Aspect Ratio	2.7
3-1	Clothing Insulation Necessary for Various Levels of Comfort at a Given Temperature During Light, Mainly Sedentary Activities	3.3
3-2	Comfort Zone	3.6
3-3	Range of Average Air Movements Permitted in The Summer and Extended Summer Zones	3.7
3-4	Optimum Operative Temperatures for Active People in Low Air Movement Environments	3.9
3-5	Percentage of Occupants Objecting to Drafts in Air-conditioned Rooms (I-P)	3.11
3-6	Percentage of Occupants Objecting to Drafts in Air-conditioned Rooms (SI)	3.11
3-7	Surface (Coanda) Effect	3.13
3-8	Outlet Velocity and Air Direction Diagrams for Stack Heads With Expanding Outlets	3.16
3-9	Air Motion Characteristics of Group A Outlets	3.17
3-10	Air Motion Characteristics of Group B Outlets	3.18
3-11	Air Motion Characteristics of Group C Outlets	3.19
3-12	Air Motion Characteristics of Group D Outlets	3.19
3-13	Air Motion Characteristics of Group E Outlets	3.20
4-1	Duct Pressure Class Designation (I-P)	4.7
4-1M	Duct Pressure Class Designation (SI)	4.8
4-2	Symbols for Ventilation and Air Conditioning (I-P)	4.9
4-2M	Symbols for Ventilation and Air Conditioning (SI)	4.10
5-1	Capillary Action	5.2
5-2	Velocity Profile	5.3
5-3	Relation Between Friction Factor and Reynolds Number	5.4
5-4	Velocity Profiles of Flow in Ducts	5.7
5-5	Separation in Flow in a Diffuser	5.7
5-6	Changing Velocity Profiles At a Mitered Elbow	5.8
5-7	Effect of Duct Length On Damper Action	5.8
5-8	Part Duct Friction Loss Chart (I-P)	5.15
5-9	Part Duct Friction Loss Chart (SI)	5.16
5-10	Pressure Changes During Flow-in Ducts	5.24
5-11	Return Air Duct Example	5.24
5-12	To Calculate Splitter Vane Spacing for a Smooth Radius Rectangular Elbow	5.27
5-13	Turning Vanes Research	5.28
5-14	Turbulence Caused By Improper Mounting and Use of Turning Vanes	5.29
5-15	Proper Installation of Turning Vanes	5.30
5-16	AMCA Damper Tests	5.32
5-17	Duct Obstructions	5.32
5-18	Example 5-5 Fan/System Curve	5.34
5-19	Duct Leakage Classifications	5.35
5-20	Rectangular Elbow 90 Degree Throat, 90 Degree Heel	5.40
5-21	Different Configuration Elbow Research	5.41
5-22	End Tap Research	5.42
5-23	Fan Total Pressure (TP)	5.43
5-24	Fan Static Pressure (SP)	5.43
5-25	Fan Velocity Pressure (V_p)	5.43
5-26	Tip Speed	5.44
5-27	Centrifugal Fan Components	5.45
5-28	Axial Fan Components	5.46
5-29	Method of Obtaining Fan Performance Curves	5.47
5-30	Characteristic Curves for FC Fans	5.47
5-31	Characteristic Curves for BI Fans	5.48



5-32	Characteristic Curves for Airfoil Fans	5.48
5-33	Tubular Centrifugal Fan	5.48
5-34	Characteristic Curves for Tubular Centrifugal Fans	5.49
5-35	Characteristic Curves for Propeller Fans	5.49
5-36	Characteristic Curves for Vaneaxial Fans	5.49
5-37	Application of the Fan Laws	5.50
5-38	Centrifugal Fan Performance Table (I-P)	5.51
5-39	Centrifugal Fan Performance Table (Metric Units)	5.51
5-40	System Resistance Curve	5.52
5-41	Fan Curve Plots	5.53
5-42	Normalized Duct System Curves	5.54
5-43	Operating Point	5.54
5-44	Variations from Design – Air Shortage	5.54
5-45	Effect of 10 Percent Increase in Fan Speed	5.55
5-46	Interactions of System Curves and Fan Curve	5.56
5-47	Effect of Density Change (Constant Volume)	5.56
5-48	Effect of Density Change (Constant Static Pressure)	5.57
5-49	Effect of Density Change (Constant Mass Flow)	5.58
5-50	Duct System Curve Not At Design Point	5.59
5-51	AMCA Fan Test – Pitot Tube	5.60
5-52	Establishment of a Uniform Velocity Profile	5.61
5-53	Effects of System Effect	5.62
5-54	System Effect Curves for Inlet Duct Elbows – Axial Fans	5.63
5-55	Sample ASHRAE Fan System Effect “Loss Coefficients”	5.68
5-56	Changes from System Effect	5.69
5-57	Sensitivity of System Volume to Locations of Building Openings, Intakes, and Exhausts	5.70
5-58	Building Surface Flow Patterns	5.71
5-59	Pressure Difference Due to Stack Effect	5.72
5-60	Air Movements Due to Normal and Reverse Stack Effect	5.73
6-1	System Effect Curves	6.2
6-2	Controlled Diffusion and Establishment of a Uniform Velocity Profile in a Straight Length of Outlet Duct	6.3
6-3	Outlet Duct Elbows	6.5
6-4	Parallel Versus Opposed Dampers	6.7
6-5	Typical HVAC Unit Connections	6.8
6-6	Typical Inlet Connections for Centrifugal and Axial Fans	6.8
6-7	Non-uniform Flow into a Fan Inlet Induced by a 90 Degree Round Section Elbow – No Turning Vanes	6.9
6-8	Non-uniform Flow Induced into Fan Inlet by a Rectangular Inlet Duct	6.9
6-9	System Effects for Various Mitered Elbows Without Vanes	6.10
6-10	System Effects for Square Duct Elbows	6.11
6-11	Example of a Forced Inlet Vortex (Spin-Swirl)	6.12
6-12	Inlet Duct Connections Causing Inlet Spin	6.12
6-13	Corrections for Inlet Spin	6.13
6-14	AMCA Standard 210 Flow Straightener	6.13
6-15	System Effect Curves for Fans Located in Plenums and Cabinet Enclosures and for Various Wall to Inlet Dimensions	6.14
6-16	Enclosure Inlet Not Symmetrical With Fan Inlet, Prerotational Vortex Induced	6.14
6-17	Flow Condition of 6-16 Improved With a Splitter Sheet	6.14
6-18	Centrifugal Fan Inlet Box	6.15
6-19	Free Inlet Area Plane – Fan With Inlet Collar	6.16
6-20	Free Inlet Area Plane – Fan Without Inlet Collar	6.16
6-21	Typical Normalized Inlet Valve Control Pressure – Volume Curve	6.17
6-22	Common Terminology for Centrifugal Fan Appurtenances	6.18
7-1	Duct Systems for Duct Sizing Examples 1 and 2	7.5
7-2	Supply Air Duct System for Sizing Example 3	7.23
7-3	System “A” – Sized by Equal Friction Method	7.27
7-4	System “B” – Modified by Semi-extended Plenum Concept	7.28



7-5	Duct Sizing Work Sheet (I-P)	7.29
7-6M	Duct Systems for Duct Sizing Examples 1 and 2 (SI)	7.33
7-7M	Supply Air Duct System for Sizing Example 3	7.47
7-8M	Systems "A" Sized by Equal Friction Method	7.53
7-9M	"B" Modified by Semi-Extended Plenum Concept	7.54
7-10	Duct Sizing Work Sheet (I-P)	7.55
7-10M	Duct Sizing Work Sheet (SI)	7.56
8-1	System Pressure Loss Check List	8.3
8-2	Volume Dampers (*Based upon AMCA Certified Volume Dampers)	8.8
8-3	Backdraft or Relief Dampers	8.8
8-4	2-hour Fire & Smoke Dampers (Based on AMCA Certified Fire Dampers)	8.8
8-5	Heating Coils With 1 Row	8.9
8-6	Heating Coils With 2 Rows	8.9
8-7	Heating Coils With 3 Rows	8.9
8-8	Heating Coils With 4 Rows	8.9
8-9	Cooling Coils (Wet) 4 Row	8.10
8-10	Cooling Coils (Wet) 6 Row	8.10
8-11	Cooling Coils (Wet) 8 Row	8.10
8-12	Air Monitor Device	8.10
8-13	Louvers with 45° Blade Angle (*Based on AMCA Certified Louvers)	8.11
8-14	3 Rectangular Sound Traps – 3 Foot (1M)	8.11
8-15	Rectangular Sound Traps – 5 Foot (1.5M)	8.11
8-16	Rectangular Sound Traps – 7 Foot (2M)	8.11
8-17	Rectangular Sound Traps – 10 Foot (3M)	8.12
8-18	Round Sound Traps	8.12
8-19	Eliminators Three Bend	8.12
8-20	Air Washer	8.12
8-21	Screens	8.13
8-22	Air-to-Air Plate Exchangers (Modular)	8.13
8-23	Air-to-Air Single Tube Exchangers	8.13
8-24	Rotary Wheel Exchanger	8.13
8-25	Multiple Tower Energy Exchangers	8.14
8-26	Dry Air Evaporative Cooler	8.14
8-27	Recommended Criteria for Louver Sizing	8.17
9-1	Design Considerations for Diffuser Layouts and Balancing Damper Locations	9.2
9-2	Duct Design Considerations for Suggested Balancing Damper Locations	9.3
9-3	Design Considerations to Minimize Airflow Turbulence and Stratification from Terminal Boxes	9.4
9-4	Fan Rating Test	9.6
9-5	Typical Velocity Profiles Encountered in Velocity Pressure Measurement Planes	9.9
10-1	Source, Path, and Receiver	10.1
10-2	Mechanical Equipment Room Adjacent to Office Area	10.2
10-3	Illustration of Well- Balanced Hvac Sound Spectrum for Occupied Spaces	10.3
10-4	Frequency Ranges of the Most Likely Sources of Acoustical Complaints	10.4
10-5	Frequency At Which Different Types of Mechanical Equipment Generally Control Sound Spectra	10.4
10-6	Dissipative Passive Duct Silencers	10.9
10-7	Active Duct Silencer	10.9
10-8	External Duct Lagging on Rectangular Ducts	10.10
10-9	Breakout and Break-In of Sound in Ducts	10.11